

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : <b>G06F 17/60</b>		A1	(11) International Publication Number: <b>WO 00/62223</b>
			(43) International Publication Date: 19 October 2000 (19.10.00)
(21) International Application Number: <b>PCT/US00/40077</b>			(81) Designated States: AE, AG, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, DZ, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (Utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 29 March 2000 (29.03.00)			
(30) Priority Data: 60/128,557 9 April 1999 (09.04.99) US 09/377,447 19 August 1999 (19.08.99) US 09/377,322 19 August 1999 (19.08.99) US			
(71) Applicant: AMAZON.COM, INC. [US/US]; 1200 12th Avenue South, Suite 1200, Seattle, WA 98144 (US).			
(72) Inventors: BEZOS, Jeffrey, P.; 1516 2nd Avenue, Seattle, WA 98101 (US). SPIEGEL, Joel, R.; 14026 227th Avenue NE, Woodinville, WA 98072 (US). MCAULIFFE, Jon; 615 Bellevue Avenue East #101, Seattle, WA 98102 (US).			
(74) Agent: NATAUPSKY, Steven, J.; Knobbe, Martens, Olson & Bear, LLP, 16th Floor, 620 Newport Center Drive, Newport Beach, CA 92660-8016 (US).			Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: SYSTEMS AND METHODS FOR ASSISTING USERS IN SELECTING AND EVALUATING ITEMS FROM AN ELECTRONIC CATALOG



(57) Abstract

A Web based system provides informational service components (80B-80E) for assisting customers in selecting products or other types of items from an electronic catalog of a merchant. Users of the system can create and join user communities such as communities based on user hobbies, localities, professions, and organizations. The system also supports implicit membership communities that are based on email addresses (e.g., all users having a "nasa.com" email address), shipping/billing addresses, and other known user information. Using purchase history data collected for online users, the system automatically identifies and generates lists (86A) of the most popular items (and/or items that are becoming popular) within particular communities and makes such information available to users for viewing.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TC	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**SYSTEMS AND METHODS FOR ASSISTING USERS IN SELECTING  
AND EVALUATING ITEMS FROM AN ELECTRONIC CATALOG**

**PRIORITY CLAIM**

5           This application claims the benefit of U.S. Provisional Application No. 60/128,557, filed April 9, 1999.

**FIELD OF THE INVENTION**

          This invention relates to electronic commerce and information filtering. More specifically, this invention relates to information processing methods for assisting online users in identifying and evaluating items from a database of items based on user purchase histories or other historical data.

10

**BACKGROUND OF THE INVENTION**

          Web sites of online merchants commonly provide various types of informational services for assisting users in evaluating the merchants' product offerings. Such services can be invaluable to an online customer, particularly if the customer does not have the opportunity to physically inspect the merchants' products or talk to a salesperson.

          One type of service involves recommending products to users based on personal preference information. Such  
15       preference information may be specified by the user explicitly, such as by filling out an online form, or implicitly, such as by purchasing or rating products. The personalized product recommendations may be communicated to the customer via an email message, a dynamically-generated Web page, or some other communications method.

          Two types of algorithmic methods are commonly used to generate the personalized recommendations —  
20       collaborative filtering and content-based filtering. Collaborative filtering methods operate by identifying other users with similar tastes, and then recommending products that were purchased or highly rated by such similar users. Content-based filtering methods operate by processing product-related content, such as product descriptions stored in a database, to identify products similar to those purchased or highly rated by the user. Both types of methods can be combined within a single system.

          Web sites also commonly implement services for collecting and posting subjective and objective information  
25       about the product tastes of the online community. For example, the Web site of Amazon.com, the assignee of the present application, provides a service for allowing users to submit ratings (on a scale of 1-5) and textual reviews of individual book, music and video titles. When a user selects a title for viewing, the user is presented with a product detail page that includes the title's average rating and samples of the submitted reviews. Users of the site can also access lists of the bestselling titles within particular product categories, such as "mystery titles" or "jazz CDs."

30

**SUMMARY OF THE INVENTION**

          One problem with the above-described methods is that they fail to take into consideration the level of acceptance the merchant's products have attained within specific user communities. As a result, products that are very popular within the communities to which the user belongs or is affiliated may never be called to the user's attention. For example, a programming book that has attained disparate popularity among Microsoft Corporation programmers may never be called  
35       to the attention of other programmers, including other programmers at Microsoft. Even where such products are known to

the user, the user's ignorance of a product's level of acceptance within specific communities, and/or the user's inability to communicate with users who are familiar with the product, can contribute to a poor purchase decision.

The present invention addresses these and other problems by providing various computer-implemented services for assisting users in identifying and evaluating items that have gained acceptance within particular user communities. The services are preferably implemented as part of a Web site system, but may alternatively be implemented as part of an online services network, interactive television system, or other type of information system. In one embodiment, the services are provided on the Web site of an online store to assist users in identifying and evaluating products, such as book titles.

The communities may include explicit membership communities that users can join through a sign-up page. The explicit membership communities may include, for example, specific universities, outdoors clubs, community groups, and professions. Users may also have the option of adding explicit membership communities to the system, including communities that are private (not exposed to the general user population). The communities may additionally or alternatively include implicit membership communities for which membership is determined without any active participation by users. Examples of implicit membership communities include domain-based communities such as *Microsoft.com Users* (determined from users' email addresses), geographic region based communities such as *New Orleans Area Residents* (determined from users' shipping addresses), and communities for which membership is based on users' purchase histories.

In accordance with one aspect of the invention, a service is provided for automatically generating and displaying community-based popular items lists. The popular items lists are preferably in the form of bestseller lists that are based on sales activities over a certain period of time, such as the last two months. By viewing these lists, users can readily identify the bestselling products within specific communities. In one embodiment, the bestseller lists for the communities of which the user is a member are automatically displayed on a personalized Web page. The bestseller lists could also be communicated by email, fax, or another communications method.

One feature of the invention involves generating bestseller lists that are based solely on Internet domains, without requiring any active user participation. These domain-based bestseller lists may be displayed automatically on the home page or other area of the Web site.

Another feature of the invention involves generating and displaying bestseller lists for "composite communities," which are communities formed from multiple implicit and/or explicit membership communities. Using this feature, a user can, for example, view a bestseller list for the composite community *All U.S. Bicycle Clubs*, or *Domains of all Software Companies*. In one embodiment, users can define their own, personal composite communities (such as by selecting from a list of non-composite communities) to create custom bestseller lists.

In accordance with another aspect of the invention, a service is provided for notifying users interested in particular products of other users that have purchased the same or similar products. In one embodiment, the service is implemented by providing user contact information on product detail pages. For example, when a user views a product detail page for a particular product (such as a kayak), the detail page may be customized to include the names and email addresses of other members of the user's community (such as a kayaking club) that recently purchased the same product.

If any of these other members is online, the user may be presented the option to send an instant message or otherwise chat online with such members. In one implementation, users can opt to expose their contact information to other community members (and thus participate in the service) on a community-by-community basis. A variation of this service involves notifying users interested in particular merchants (e.g., sellers on an online auction site) of the contact information of other users (preferably fellow community members) that have engaged in business with such merchants.

In accordance with yet another aspect of the invention, a notification service is provided for informing users of popular products within their respective communities. The popular products may be identified, for example, based on the popularity of the product within the community relative to the product's popularity within the general user population, or based simply on the number of units recently purchased within the community relative to the number of community members. In one embodiment, users can also request to be notified of all purchases made within their respective communities. The popular product and purchase event notifications are preferably sent by email (to community members that have not yet purchased the product), but may alternatively be communicated using a personalized Web page of other method. The notifications may include information for assisting users in evaluating the products, such as the number of community members that have purchased the product and/or contact information of such other users.

In accordance with another aspect of the invention, the purchase histories of users are processed to identify the "characterizing purchases" of a community, and these characterizing purchases are used to recommend items within that community. Specifically, the purchase history data of the community is compared to the purchase history data of a general user population to identify a set of items purchased within the community that distinguish the community from the general user population. Items are then implicitly or explicitly recommended to members of the community from this set, such as through popular items lists or email notifications.

The various features of the invention can also be used in the context of a system in which users merely view, download, and/or rate items without making purchases. In such systems, each viewing, downloading and/or rating event (or those that satisfy certain criteria) can be treated the same as a purchase event.

#### BRIEF DESCRIPTION OF THE DRAWINGS

A set of services which implement the various features of the invention will now be described with reference to the drawings of a preferred embodiment, in which:

Figure 1 illustrates an example sign-up page for specifying community memberships and service preferences;

Figure 2 illustrates a personalized community bestsellers page;

Figure 3 illustrates an example product (book) detail page which includes contact information of other community members that have purchased the product;

Figure 4 illustrates an example hotseller notification email message;

Figure 5 is an architectural drawing which illustrates a set of components which may be used to implement the community bestseller lists, hotseller notification, and contact information exchange services;

Figure 6 illustrates an offline process for generating the community bestseller lists table and the product-to-member tables of Figure 5;

Figure 7A and 7B illustrate an online (real time) process for generating personalized community bestseller pages of the type shown in Figure 2.

Figure 8 illustrates an online process for generating personalized product detail pages of the type shown in Figure 3.

5 Figure 9 illustrates an offline process for generating email notifications of hot-selling products as in Figure 4.

Figure 10 illustrates a process for notifying community members of purchases made within the community.

#### DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

10 A set of online services referred to herein as "Community Interests" will now be described in detail. The services will initially be described with reference to example screen displays which illustrate the services from the perspective of end users. A set of example data structures and executable components that may be used to implement the services will then be described with reference to architectural and flow diagrams.

15 The illustrated screen displays, data structures and processing methods used to implement the disclosed functions are largely a matter of design choice, and can be varied significantly without departing from the scope of the invention. In addition, although multiple different services will be described as part of a single system, it will be recognized that any one of these services could be implemented without the others. Accordingly, the scope of the invention is defined only by the appended claims.

20 To facilitate an understanding of one practical application, the Community Interests services will be described primarily in the context of a hypothetical system for assisting users of a merchant Web site, such as the Web site of Amazon.com, in locating and evaluating book titles within an electronic catalog. It will be recognized, however, that the services and their various features are also applicable to the marketing and sales of other types of items. For example, in other embodiments, the items that are the subject of the services could be cars sold by an online car dealer, movies titles rented by an online video store, computer programs or informational content electronically downloaded to users' computers, or stock and mutual fund shares sold to online investors. Further, it should be understood that the "purchases" referred to herein need not involve an actual transfer of ownership, but could rather involve leases, licenses, rentals, 25 subscriptions and other types of business transactions.

30 As with the Amazon.com Web site, it will be assumed that the hypothetical Web site provides various services for allowing users to browse, search and make purchases from a catalog of several million book, music and video titles. It is also assumed that information about existing customers of the site is stored in a user database, and that this information typically includes the names, shipping addresses, email addresses, payment information and purchase histories of the customers. The information that is stored for a given customer is referred to collectively as the customer's "user profile."

35 The Community Interests services operate generally by tracking purchases of books within particular user communities, and using this information to assist potential customers in locating and evaluating book titles. The services can also be used with other types of products. The communities preferably include both "explicit membership communities" that users actively join, and "implicit membership communities" that are computer or otherwise identified from information known about the user (e.g., stored in the user database). Examples of implicit membership communities

include domain-based communities such as *Microsoft.com Users* and geographic region base communities such as *New Orleans Area Residents*; memberships to these two types of communities may be determined from user email addresses and shipping addresses, respectively.

5 The system may also use implicit membership communities for which membership is based in-whole or in-part on the purchase activities of the users. For example, the implicit membership community "fishermen" may include all users that have purchased a book about fishing. Where purchase histories are used, the communities may be defined or inferred from such purchase histories using clustering techniques.

10 In other embodiments, the various features of the invention may be implemented using only one of these two types of communities (explicit membership versus implicit membership). In addition, the services may be implemented using "hybrid" communities that are based on information known about the user but that are actively joined; for example, the user could be notified that a community exists which corresponds to his email domain or purchase history and then given the option to join.

The Community Interests system includes four different types of services. The first, referred to herein as "Community Bestsellers," involves generating and displaying lists of the bestselling titles within specific communities. 15 Using this feature, users can identify the book titles that are currently the most popular within their own communities and/or other communities. The bestselling titles are preferably identified based on the numbers of units sold, but could additionally or alternatively be based on other sales related criteria. In other embodiments, the lists may be based in-whole or in-part on other types of data, such as user viewing activities or user submissions of reviews and ratings.

20 One preferred method that may be used to identify bestselling or popular titles involves monitoring the "velocity" of each product (the rate at which the product moves up a bestsellers list) or the "acceleration" of each product (the rate at which the velocity is changing, or at which sales of the product are increasing over time). This method tends to surface products that are becoming popular. To identify the popular items within a particular community, the velocity or acceleration of each product purchased within that community can be compared to the product's velocity or acceleration within the general user population. Velocity and acceleration may be used both to generate bestseller lists and to identify 25 "hot" products to proactively recommend to users (as discussed below).

The second service, referred to herein as "Contact Information Exchange," involves informing a user that is viewing a particular product of other users within the same community that have purchased the same or a similar product. For example, when a user within *Netscape.com Users* views a product detail page for a particular book on programming, the page may include the names and email addresses of other Netscape.com users that have recently purchased the title, 30 and/or an instant messaging box for sending a message to any such user that is currently online. To protect the privacy of the recent purchasers, their names and/or email addresses may be masked, in which case an email alias or a bulletin board may be provided for communicating anonymously. This feature may also be used to display the contact information of other users that have bought from or otherwise conducted business with a particular seller.

The third service, referred to as "Hotseller Notification," automatically notifies users of titles that have become 35 unusually popular within their respective communities. For example, a user within a particular hiking club might be notified

that several other users within his club have recently purchased a new book on local hiking trails. In one embodiment, a community's "hotsellers" are identified by comparing, for each title on the community's bestseller list, the title's popularity within the community to the title's popularity within the general user population. The popularities of the titles are preferably based at least in-part on numbers of units sold, but may be additionally or alternatively be based other types of criteria such as user viewing activities or user submissions of reviews and ratings.

One such method that may be used to identify the hotsellers (or for generating community recommendations in general) involves applying an algorithm referred to as the censored chi-square recommendation algorithm to the purchase or other history data of users. The effect of the censored chi-square recommendation algorithm (when applied to purchase history data) is to identify a set of "characterizing purchases" for the community, or a set of items purchased within the community which distinguishes the community from a general user population (e.g., all customers). The results of the algorithm may be presented to users in any appropriate form, such as a community popular items list, a notification email, or a set of personal recommendations. The censored chi-square algorithm is described in the attached appendix, which forms part of the disclosure of the specification. Another such method that may be used to identify the community hotsellers involves comparing each title's velocity or acceleration within the community to the titles's velocity or acceleration within the general user population.

A fourth service, referred to as "Purchase Notification," automatically notifies users of purchases (including titles and the contact information of the purchaser) made within their respective communities. This service may, for example, be made available as an option where the community members have all agreed to share their purchase information. Alternatively, users may have the option to expose their purchases to other community members on a user-by-user and/or item-by-item basis.

Figure 1 illustrates the general form of a sign-up page that can be used to enroll with the Community Interests services. Although some form of enrollment is preferred, it will be recognized that Community Bestsellers, Hotseller Notification, Contact Information Exchange and Purchase Notification services can be implemented without requiring any active participation by the site's users. For example, all four services could be based solely on the Internet domains of the users, without requiring users to actively join communities. In addition, the communities could be defined automatically based on correlations between purchases; for example, all users that purchased more than X books within the "Business and Investing" category could automatically be assigned to a Business and Investing community.

As illustrated by Figure 1, the sign-up page includes drop-down lists 30 for allowing the user to specify membership in one or more explicit membership communities. The communities that are presented to the user are those that are currently defined within the system. As described below, new communities may be added by system administrators, regular users, or both. In some cases, the drop-down lists 30 may be filtered lists that are generated based on information known about the particular user. For example, the selections presented in the "local community groups" and "local outdoors clubs" lists may be generated based on the user's shipping address.

Any of a variety of other interface methods could be used to collect community membership information from users. For example, rather than having the user select from a drop-down list, the user could be prompted to type-in the



names of the communities to which the user belongs. When a typed-in name does not match any of the names within the system, the user may be presented with a list of "close matches" from which to choose. Users may also be provided the option of viewing the membership lists of the communities and specifying the users with which to share information.

As illustrated by the link 32 and associated text in Figure 1, users may also be given the opportunity to add new communities to the system. In the illustrated embodiment, a user wishing to add a new community has the option of designating the community as "private," meaning that the community's existence and/or data will not be exposed to the general public. Private communities may be useful, for example, when a closed group of users wishes to privately share information about its purchases. Upon creating a private community, the user may, for example, be prompted to enter the email addresses of prospective members, in which case the system may automatically send notification emails to such users. Through a similar process, companies and organizations may be provided the option of designating their domain-based communities as private.

The sign-up page also includes check boxes 36-38 for allowing users to participate in the Contact Information Exchange, Hotseller Notification, and Purchase Notification services, respectively. In each case, the user may select a corresponding link 40-42 to an associated form page (not shown) to limit participation to specific communities and/or product categories. Each user may also be given the option to expose his or her purchases and/or contact information to others on a user-by-user basis.

When the user selects the submit button 46, the user may be asked certain questions that pertain to the selected communities, such as university graduation dates and majors. The user may also be prompted to enter authentication information that is specific to one or more of the selected communities. For example, the user may be asked to enter a community password (even if the community is not private), or may be asked a question that all members of the group are able answer. A community may also have a designated "group administrator" that has the authority to remove unauthorized and disruptive users from the group.

The user's community selections, community data, and service preferences are recorded within the user's profile. Also stored within the user's profile are any domain-based or other implicit membership communities of which the user is a member. The user's community membership profile may also be recorded within a cookie on the user's machine; this reduces the need to access the user database on requests for Web pages that are dependent on this membership profile. One method which may be used to store such information within cookies is described in U.S. provisional appl. no. 60/118,266, the disclosure of which is hereby incorporated by reference.

Figure 2 illustrates the general form of a personalized Web page (referred to herein as the "community bestsellers page") which may be used to display the community bestseller lists. This page may be accessed, for example, by selecting a link from the site's home page. Community bestseller lists could additionally or alternatively be provided on other areas of the site. For example, the bestseller list of the Nasa.com domain could automatically be displayed on the home page for any user that has purchased a book on space exploration; or, when a user from the domain mckinsey.com makes a purchase, the user might be presented the message "would you like to see the bestsellers from the McKinsey & Co. group?"

In the Figure 2 example, it is assumed that the user is a member of the explicit membership community *Cascade Bicycle Club* and the implicit membership community *Microsoft.com Users*. For each of these communities (as well as any other communities of which the user is a member), the page includes a hypertextual listing of top selling book titles. The methods used to generate these lists are described below. Users may also be given the option (not shown) to view all titles purchased within their respective communities.

As depicted by the drop-down list 50 in Figure 2, the user may also be provided the option of viewing the bestseller lists of other communities, including communities of which the user is not a member. As in this example, the listing of other communities may be ordered according to the known or predicted interests of the user. A community directory structure or search engine may also be provided for assisting users in finding communities and their bestseller lists.

As further illustrated by Figure 2, some of the communities may be "composite" communities that are formed as the union of other, smaller communities. In this example, the composite communities are *All U.S. Bicycle Clubs*, which consists of all regional and other bicycle club communities in the U.S., and *Domains of All Software Companies*, which consists of domains-based communities of selected software companies. Other examples include *All Law Students* and *All Physicians*. Bestseller lists for composite communities are particularly helpful for identifying book titles that are popular across a relatively large geographic region. For example, a user searching for a book on biking the United States, or on biking in general, would more likely find a suitable book in the *All U.S. Bicycle Clubs* bestseller list than in the *Cascade Bicycle Club* bestseller list.

In the preferred embodiment, a user can be a member of a composite community only through membership in one of that composite community's member, base communities. (A "base community," as used herein, is any non-composite community, regardless of whether it is part of a composite community.) The composite communities that are exposed to the general user population could be defined by system administrators; alternatively, the composite communities could be defined automatically, such as by grouping together all base communities that have certain keywords in their titles.

In one implementation, users can also define their own, "personal" composite communities, such as by selecting from a list (not shown) of base communities and assigning a community name. Using this feature, a user could, for example, define a composite community which consists of all kayaking clubs on the West Coast or of a selected group of hi-tech companies. If the user has defined a personal composite community, that community's bestseller list is preferably automatically displayed on the user's community bestsellers page (Figure 2). As with the user's community membership profile, the definitions of any personal composite communities specified by the user may be stored within a cookie on the user's machine.

As further illustrated by Figure 2, users can also view a bestseller list of the general user population (e.g., all Amazon.com users). The general user population is treated as special type of community (i.e., it is neither a base community nor a composite community), and is referred to herein as the "global community."

Another option (not illustrated) involves allowing users to specify subsets of larger communities using demographic filtering. For example, a user within the MIT community might be given the option to view the bestselling titles among MIT alumnus who fall within a particular age group or graduated a particular year.

Figure 3 depicts an example product (book) detail page which illustrates one possible form of the Contact Information Exchange service. Detail pages of the type shown in Figure 3 can be located using any of a variety of navigation methods, including performing a book search using the site's search engine or navigating a subject-based browse tree. The contact information 58 of other community members that purchased the displayed book title (preferably within a certain period of time), or possibly similar titles, is displayed at the bottom of the page. In other embodiments, the contact information may be displayed without regard to community membership.

In the illustrated embodiment, the contact information 58 includes the name, email address and common communities of the users, although telephone numbers, residence addresses, chat boxes and other types of contact information could additionally or alternatively be included. In the example shown in Figure 3, the user viewing the book detail page might contact such other users to ask their opinions about the book, or about the bike tours described therein. In addition, the contact information might be useful for arranging a group trip. As depicted in Figure 3, the page may also include a link 60 or other type of object for sending an email or other message to the fellow community member.

In one embodiment (not illustrated), once the relevant set of "prior purchasers" has been identified, the system uses well known methods to determine whether any of these other users is currently online. If one or more of the prior purchasers is online, the user is presented an option to send an instant message to prior purchaser(s), and/or to set up a private chat room for communicating with prior purchasers. Thus, the contact information may simply be in the form of an instant messaging box or other option for chatting online with specific users.

In other embodiments, the various contact information exchange features may be used to assist users in evaluating the reputation of a particular merchant. For example, when a user views an auction of a particular seller, the contact information of other community members (or possibly non-community members) that bought from that seller may be displayed, or an option could be provided to chat with any such users that are currently online. Where the merchant has its own Web site, the contact information could, for example, be displayed as Web site metadata using a browser add-on of the type provided by Alexa Internet of San Francisco, California.

Any of a variety of methods could be used for allowing the prospective purchaser to communicate with the listed contacts anonymously. For example, as indicated above, the email addresses of the contacts could be special aliases created for communicating anonymously (in which case the prospective purchaser may similarly be assigned an email alias for the contacts to respond), or the prospective purchaser and the contacts could be given a link to a private bulletin board page.

Figure 4 illustrates an example of an email document which may be used to notify community members of a hot-selling book title. Similar notifications may be provided to users through customized Web pages and other communications methods. As described below, the email document is preferably sent to all participating members of the community that have not already purchased the book.

In the illustrated example, the email document includes a textual description 66 which, among other things, includes a synopsis of the book title and informs the user of the level of acceptance the title has attained within the community. The description also includes a hypertextual link 68 to the title's detail page on the site. In addition, if the recipient user participates in the Contact Information Exchange program, the email document preferably includes a listing  
5 70 of the contact information of other community members that have purchased the book.

Email notifications sent by the Purchase Notification service (not shown) may likewise include a synopsis of the purchased product and a link to the product's detail page. In addition, where the purchaser has elected to participate in the Contact Information Exchange program, the email document may include the purchaser's contact information (and possibly the contact information of other community members who have purchased the product); for example, when User A in  
10 Community A purchases an item, an email may be sent to other members of Community A with a description of the product and User A's contact information.

Having described representative screen displays of the Community Interests services, a set of Web site components that may be used to implement the services will now be described in detail.

Figure 5 illustrates a set of Web site system components that may be used to implement the above-described  
15 features. The Web site system includes a Web server 76 which accesses a database 78 of HTML (Hypertext Markup Language) and related content. The HTML database 78 contains, among other things, the basic HTML documents used to generate the personalized sign-up, community bestsellers, and product detail pages of Figures 1-3. The Web server 76 accesses service code 80, which in-turn accesses a user database 82, a community database 84, a bibliographic database of product data (not shown), and a database or other repository of community data 86. The various databases are shown  
20 separately in Figure 1 for purposes of illustration, but may in practice be combined within one or more larger database systems. The service code 80 and other executable components may, for example, run on one or more Unix or Windows NT based servers and/or workstations.

The community data 86 includes a "community bestseller lists" table 86A which contains, for the global community and each base community, a listing of the currently bestselling book titles. In some implementations, the listing  
25 for the global community is omitted. In the illustrated embodiment, each entry 88 in each bestseller list includes: (a) the product ID (ProdID) of a book title, and (b) a count value which represents, for a given time window, the number of copies purchased by members of the community. The product IDs may be assigned or processed such that different media formats (e.g., paperback, hardcover, and audio tape) of the same title are treated as the same item. As described below, the community bestseller lists table 86A is used both for the generation of bestseller lists and the generation of hot seller  
30 notifications.

The community data 86 also includes, for each base community, a respective product-to-member mapping table 86B which maps products to the community members that have recently purchased such products (e.g., within the last 2 months). For example, the entry for product Prod\_A within the table 86A for Community A is in the form of a listing of the user IDs and/or contact information of members of Community A that have recently purchased that product. In the

preferred embodiment, only those community members that have opted to participate in the Contact Information Exchange service are included in the lists.

As mentioned above, the user database 82 contains information about known users of the Web site system. The primary data items that are used to implement the Community Interests service, and which are therefore shown in Figure 5, are the users' purchase histories, community memberships, service preference data (e.g., whether or not the user participates in the Contact Information Exchange and Hotseller Notification services), and shipping information. Each user's purchase history is in the general form of a list of product IDs of purchased product, together with related information such as the purchase date of each product and whether or not the purchase was designated by the user as a "gift." Purchases designated as gifts may be ignored for purposes of evaluating community interests. Each user's database record also preferably includes a specification of any personal composite communities the user has defined, for viewing customized bestseller lists.

With further reference to Figure 5, the community database 84 contains information about each base community (including both explicit and implicit membership base communities when both types are provided) that exists within the system. This information may include, for example, the community name, the type of the community (e.g., college/university, local community group, etc.), the location (city, state, country, etc.) of the community, whether the community is private, whether the community participates in the Purchase Notification service, any authentication information required to join the community, and any community policies (e.g., by joining, all users agree to expose their purchases to other members). For implicit membership communities, the database 84 may also include information about the user database conditions which give rise to membership. As indicated above, the information stored within the communities database 84 may be generated by end users, system administrators, or both.

The community database 84 also includes information about any composite communities that have been defined by system administrators. For each composite community, this information may include, for example, the community name and a list of the corresponding base communities. For example, for the *All Bicycle Clubs* community, the database would contain this name and a list of all existing bicycle club base communities.

As depicted by Figure 5, the community database 84 may also contain information about relationships or associations between base communities. This information may be specified by system administrators, and may be used to identify similar communities for display purposes. For example, when a user of the *Microsoft.com Users* community views the community bestsellers page (Figure 2), the associated community *Netscape.com Users* may automatically be displayed at the top of the drop-down list 50, or its bestseller list be displayed on the same page.

As illustrated by Figure 5, the service code 80 includes five basic processes 80A-80E that are used to implement the Community Interests services. (As used herein, the term "process" refers to a computer memory having executable code stored therein which, when executed by a computer processor, performs one or more operations.) Each process is illustrated by one or more flow diagrams, the figure numbers of which are indicated in parenthesis in Figure 5. The first process 80A is an off-line process (meaning that it is not executed in response to a page request) which is used to

periodically generate the tables 86A and 86B based on information stored in the user and community databases 82, 84. Processes 80B-80D use these tables to perform their respective functions.

The second process 80B is an online process which is used to generate personalized community bestsellers pages of the type shown in Figure 2. The third process 80C is an online process which is used to generate product detail pages with contact information as shown in Figure 3; and which may also be used to compile contact information to be displayed within notification emails of the type shown in Figure 4. The fourth process 80D is an offline process which is used to identify and notify users of hot-selling products within specific communities. The fifth process 80E is used to implement the Purchase Notification service.

Figure 6 illustrates the steps performed by the table generation process 80A to generate the tables 86A, 86B. The process may, for example, be executed once per day at an off-peak time. A process which updates the tables in real-time in response to purchase events may alternatively be used. In step 100, the process retrieves the purchase histories of all users that have purchased products within the last N days (e.g., 60 days). Submissions of ratings or reviews may be treated as purchases and thus included in the purchase histories. The variable N specifies the time window to be used both for generating bestseller lists and for identifying hot-selling items, and may be selected according to the desired goals of the service. Different time windows could alternatively be used for generating the bestseller lists and for identifying hot-selling items; and different time windows could be applied to different types of communities.

In step 102, the retrieved purchase histories are processed to build a list of all products that were purchased within the last N days. Preferably, this list includes any products that were purchased solely by global community members, and thus is not limited to base community purchases.

In step 104, the process uses the data structures obtained from steps 100 and 102 to generate a temporary purchase count array 104A. Each entry in the array 104A contains a product count value which indicates, for a corresponding community: product pair, the number of times the product was purchased by a member of the community in the last N days. For example, the array 104A shown in Figure 6 indicates that a total of 350 users purchased product "PROD1," and that three of those purchases came from base community "BASE\_1." A pseudocode listing of a routine that can be used to generate the array is shown in Table 1. Multiple purchases of the same product by the same user are preferably counted as a single purchase when generating the array.

TABLE 1	
For each user;	
For each product purchased by user in last N days;	
For each community of which user is a member;	
increment purchase_count(community, product)	

In step 106, the data stored in the array is used to generate the community bestseller lists. This task involves, for each base community and the global community, forming a list of the purchased products, sorting the list according to purchase counts, and then truncating the list to retain only the X (e.g., 100) top selling titles. A longer bestsellers list (e.g., the top selling 10,000 titles) may be generated for the global community, as is desirable for identifying community  
5 hot sellers.

As indicated by the parenthetical in block 106, product velocity and/or acceleration may be incorporated into the process. The velocity and acceleration values may be calculated, for example, by comparing purchase-count-ordered lists generated from the temporary table 104A to like lists generated over prior time windows. For example, a product's velocity and acceleration could be computed by comparing the product's position within a current purchase-count-ordered  
10 list to the position within like lists generated over the last 3 days. The velocity and acceleration values can be used, along with other criteria such as the purchase counts, to score and select the products to be included in the bestseller lists.

The bestseller lists are written to a table 86A of the type depicted in Figure 5, and the new table replaces any existing table. The bestsellers lists of base communities that have less than a pre-specified threshold of total sales (e.g., less than 5) may optionally be omitted from the table 86A. Bestseller lists for the composite communities defined by  
15 system administrators could also be generated as part of the Figure 6 process, or could be generated "on-the-fly" as described below.

The last two steps 108, 110 of Figure 6 are used to generate the product-to-member mapping tables 86B of Figure 5. The first step 108 of this process involves generating a temporary table (not shown) which maps base communities to corresponding members that have opted to participate in the Contact Information Exchange program ("participating members"). In step 110, this temporary table and the purchase histories of the participating members are  
20 used to generate the product-to-member mapping table 86B for each base community. The contact information of the participating members may also be stored in these tables 86B to reduce accesses to the user database 82. Although a separate table 86B is preferably generated for each base community, a single table or other data structure could be used.

Any of a variety of other types of user activity data could be monitored and incorporated into the Figure 6  
25 process as a further indication of product popularity. Such data may include, for example, "click-through" events to product detail pages, "add to shopping cart" events, and product ratings and reviews submitted by users.

Figures 7A and 7B illustrate the steps that are performed by the community bestseller processing code 80B to generate personalized community bestseller pages of the type shown in Figure 2. The first step 120 in Figure 7A involves generating a list of the communities for which bestseller lists are to be generated and displayed. If the user has already  
30 selected one or more communities from the drop down box 50 (Figure 2), these selected communities are included in this list. If the user's identity is known, the user's base communities and personal composite communities, if any, may be added to this list. If the list is empty at this point, a set of default communities may be used. User identities are preferably determined using browser cookies, although a login procedure or other authentication method could be used. In other implementations, the community bestseller lists may be displayed without regard to the user's community membership  
35 profile.

The next step 124 involves generating the bestseller lists for each of the selected communities. This process is illustrated by Figure 7B and is described below. In step 126, the process identifies any communities that are related to the user's base communities, so that these related communities can be displayed within or at the top of the drop-down list 50 (Figure 2). Any composite community which includes one of the user's base communities may automatically be included in this list. In addition, information stored in the community database 84 may be used to identify related base communities. In other implementations, this step 124 may be omitted. Finally, in step 128, the bestseller lists and the list of related communities are incorporated into the community bestsellers page.

With reference to Figure 7B, if the community is not a composite community (as determined in step 134), the community's bestseller list is simply retrieved from the table 86A (step 136). Otherwise, the bestseller lists of all of the composite community's member base communities are retrieved and merged (steps 138-142) to form the bestseller list. As part of the merging process, the product count values could optionally be converted to normalized score values (step 138) so that those communities with relatively large sales volumes will not override those with smaller sales volumes. For a given product within a given bestseller list, the score may be calculated as (product's purchase count)/(total purchase count of bestseller list). The lists are then merged while summing scores of like products (step 140), and the resulting list is sorted from highest to lowest score (step 142). If the composite community is one that has been defined by system administrators (as opposed to a personal composite community defined by the user), the resulting bestseller list may be added to the table 86A or otherwise cached in memory to avoid the need for regeneration.

As depicted in step 144, one optional feature involves filtering out from the bestseller list some or all of the products that exist within the global community's bestseller list. For example, any book title that is within the top 500 bestseller's of the general population may automatically be removed. Alternatively, such titles could be moved to a lower position within the list. This feature has the effect of highlighting products for which a disparity exists between the product's popularity within the global community versus the community for which the bestseller list is being generated. This feature may be provided as an option that can be selectively enabled or invoked by users. Products could additionally or alternatively be filtered out based a comparison of the product's velocity or acceleration within the particular community to the product's velocity or acceleration within the global community.

As illustrated by step 146, the bestseller list is truncated (such as by taking the top 10 entries) and then returned to the process of Figure 7A for incorporation into the Web page. The Figure 7B process is repeated for each community to be included within the community bestsellers page.

Figure 8 illustrates the steps that are performed by the product detail page process 80C to generate detail pages (as in Figure 3) for participants in the Contact Information Exchange program. As indicated above, product detail pages can be accessed using any of the site's navigation methods, such as conducting a search for a title. In step 150, a list of the base communities of which the user is a member is obtained — either from a browser cookie or from the user database 82. For each base community in this list, that community's product-to-member mapping table 86B (Figure 5) is accessed to identify any other users within the community that have purchased the product. In step 154, the contact information for each such user is read from the table 86B or from the user database 82. In step 156, the contact information and



associated base community names are incorporated into the product's detail page. As indicated above, an option may additionally or alternatively be provided for the requester of the page to chat with any such other users that are currently online.

Figure 9 illustrates the off-line sequence of steps that are performed by the hotseller notifications process 80D.

- 5 The general purpose of this process is to identify, within each base community, any "hotselling" products (based on pre-specified criteria), and to call such products to the attention of those within the community that have not yet purchased the products. The sequence 160-168 is performed once for each base community. In other implementations, the process could also be used to identify hot sellers in composite communities.

- 10 In step 160, the process sequences through the products in the community's bestseller list while applying the hot seller criteria to each product. If multiple products qualify as hot sellers, only the "best" product is preferably selected. In one embodiment, a product is flagged as a hot seller if more than some threshold percentage (e.g., 5 %) of the community's members have recently purchased the product, as determined from the data within the community bestseller lists table 86A. This threshold could be a variable which depends upon the number of members of the community.

- 15 In another embodiment, the position of the product within the community's bestseller list is compared to the product's position, if any, within the global community's bestseller list. For example, any title that is in one of the top ten positions within the community's list but which does not appear in the top 1000 bestsellers of the general population may automatically be flagged as a hot seller. In addition, as mentioned above, hot sellers may be identified by comparing the product's velocity or acceleration within the community to the product's velocity or acceleration within the global community. In addition, the censored chi-square algorithm described in the attached appendix may be used to identify the  
20 hot sellers. In other implementations, these and other types of conditions or methods may be combined.

- If no hot seller is found for the community (step 162), the process proceeds to the next base community (step 170), or terminates if all base communities have been processed. If a product is found, the product-to-member mapping table 86B (Figure 5) is accessed to identify and obtain the contact information of any participating members that have purchased the product (step 164). In step 166, the process generates an email document or other notification message.  
25 As in Figure 4, this message preferably includes the contact information and a description of the product. In other implementations, the notifications may be communicated by facsimile, a customized Web page, or another communications method.

- In step 168, the notification message is sent by email to each base community member who both (1) has not purchased the product, and (2) has subscribed to the email notification service. Such members may be identified by  
30 conducting a search of the user database 82. The notification messages could alternatively be sent out to all community members without regard to (1) and/or (2) above. For users that have not subscribed to the Contact Information Exchange service, the contact information may be omitted from the notification message.

- Figure 10 illustrates a sequence of steps that may be performed to implement the Purchase Notification service. This process may be implemented whenever a user completes the check-out process to purchase one or more products. In  
35 step 180, the user's profile is checked to identify any base communities in which the user participates in the Purchase

Notification service. For each such community, all other participating members are identified in step 182. In step 184, a notification message is generated which includes a description of the purchased product(s) and the name of the common community. If the user participates in the Contact Information Exchange service, the contact information of the purchaser may also be included within this message. In step 186, the notification message is sent by email to all participating members identified in step 182. Alternatively, purchase notifications that have accumulated over a period of time may be displayed when a user logs into the system.

The various community-related features described above can also be implemented in the context of a network-based personal information management system. One such system is implemented through the Web site of PlanetAll (www.planetall.com). Using this system, users can join various online communities and can selectively add members of such communities to a virtual, personal address book. In addition, each user can selectively expose his or her own personal information to other community members on a user-by-user and datum-by-datum basis. Additional details of this system are described in U.S. appl. no. 08/962,997 titled NETWORKED PERSONAL CONTACT MANAGER filed November 2, 1997, the disclosure of which is hereby incorporated by reference.

In the context of this and other types of network-based address book systems, the contacts listed within a user's address book may be treated as a "community" for purposes of implementing the above-described features. For example, a user may be given the option to view the products purchased by other users listed in his or her address book (or a particular section of the address book), or to view a bestsellers list for such users. Further, when the user views a product detail page (or otherwise selects a product), the contact information of other users within the address book that bought the same product may be displayed. Further, a user may be given the option to conduct a search of a friend's address book to locate another user that purchased a particular product.

Although this invention has been described in terms of certain preferred embodiments and applications, other embodiments and applications that are apparent to those of ordinary skill in the art, including embodiments which do not provide all of the features and advantages set forth herein, are also within the scope of this invention. Accordingly, the scope of the present invention is intended to be defined only by reference to the appended claims.

## Appendix

### 1. Overview

5 The censored chi-square recommendation algorithm constructs a set of candidate recommendations for a predefined group of customers. It then conducts a statistical hypothesis test to decide whether or not these candidate recommendations are really a result of group preferences which differ from the preferences of the overall customer base. If the conclusion is that group preferences do differ significantly from overall customer preferences, the recommendations are presented to the group.

10

The inputs to the censored chi-square algorithm are the purchases made by the group (over some time period) and the purchases made by all customers (over the same time period). Other types of events, such as item viewing, downloading and rating events, can additionally or alternatively be used.

15 The purchases of the entire customer base are used to formulate expectations about how many customers in the group will have purchased each available item, given the total number of purchases by the group. The "group purchase count" for each item is the number of customers in the group who actually purchased the item. The candidate recommendations are first restricted to be those items whose group purchase counts exceeded expectations. Of these candidates, only those items with the largest group purchase counts are then retained. These final candidates are sorted according to how  
20 much their group purchase counts exceeded expectations (subject to a normalization). The values used to sort the candidates are called the "residuals".

These residuals form the basis of a test statistic which leads to an estimate of the probability that expectations about the group are the same as expectations about all customers. If this probability is low, it is inferred that the group's  
25 preferences are significantly different from the preferences of all customers, and the recommendations are returned as output. If the probability is high, on the other hand, then little evidence exists to suggest the group's preferences differ from overall preferences, so no recommendations are returned.

### 2. Algorithm for Constructing Censored Chi-Square Recommendations

30

Let A be the set of customers in the purchase circle (community) under consideration.

With respect to the minimum lookback horizon L such that  $S_{\{.99\}}$  (defined below) is at least 5:

Define  $P = \{ \langle c, i \rangle : c \in A \text{ and } c \text{ purchased item } i \text{ at least once between today and } L \text{ periods ago} \}$

35

Let  $|P| = n$ .

Define  $I = \{ i : \text{there exists a } c \in A \text{ such that } \langle c, i \rangle \in P \}$

5 Define observed counts, expected counts, residuals and standardized residuals as follows:

$o(i) = |\{ c : c \in A \text{ and } c \text{ purchased } i \text{ within } L \}|, i \in I$

$e(i) = n \cdot \text{phat}_i$ ,  $\text{phat}_i$  is the estimated purchase probability for  $i, i \in I$

$r(i) = o(i) - e(i), i \in I$

$r\_s(i) = r(i) / \sqrt{e(i)}, i \in I$

10

Define  $I^* \subseteq I = \{ i : i \in I \text{ and } r(i) > 0 \}$

Let  $S$  be the image of  $I^*$  under  $o(i)$ . Let  $|S| = d$ .

15 Let  $S_{(1)}, S_{(2)}, \dots, S_{(d)}$  be the order statistics of  $S$ . thus  $S_{(d)}$  is the number of distinct customers who purchased the most-purchased (positive- residual) item. Note ties are common, so that a subsequence  $S_{(i)}, S_{(i+1)}, \dots, S_{(i+j)}$  may have all elements equal.

Let  $S_{\{c\}}, 0 \leq c \leq 1$ , be the  $c$ th quantile of  $S$ , that is,  $(100 \cdot c)\%$  of the other elements in  $S$  are less than or equal to  $S_{\{c\}}$ . Interpolate and break ties as necessary to determine  $S_{\{c\}}$ .

20 Let  $SR$  be the set of standardized residuals which correspond to elements of  $S$  that are  $\geq S_{\{.99\}}$ .

Let  $|SR| = m$ .

25 Let  $SR_{(1)}, \dots, SR_{(m)}$  be the order statistics of  $SR$ .

Call the desired number of recommendations  $r$ . Then the order statistic index of the final recommendation candidate is  $r^* = \max(m-r+1, 1)$ .

30 Compute  $T = \sum_{i=r^*}^m SR_{(i)}^2$

Compute the  $p$ -value of  $T$ , i.e.  $\Pr(X > T)$  where  $X \sim \chi^2(n, r^*)$ .

If the  $p$ -value achieves the desired significance level, then the recommended items for the circle, in order, are  $SR_{(m)}$ ,  
35  $SR_{(m-1)}, \dots, SR_{(r^*+1)}, SR_{(r^*)}$ .

### 3. Estimating the Sampling Distribution of the Censored Chi-Square Statistic

To construct a numerical approximation of the censored chi-square sampling distribution under the null hypothesis, we  
5 employ a statistical resampling technique called the bootstrap. The idea is straightforward. We create a group of customers by simple random sampling with replacement from the entire customer base. By construction, the expected purchase allocations of such a group follow the probability model of our null hypothesis. We emphasize that this is simply an algebraic consequence of the method used to fit the null model, and in fact the linearity of expectation guarantees that it holds algebraically regardless of any interdependencies our model ignored in the joint distribution over purchase  
10 probabilities .

We then compute the censored chi-square statistic for this random group, as presented above. We can think of the value so obtained as an approximate sample drawn from the censored chi-square's null distribution. By repeatedly (1) constructing a set of customers randomly and (2) computing its censored chi-square statistic, we approximate the so-called empirical distribution of the  $cX^2$  under the null hypothesis. Under mild to moderate probabilistic conditions, the  
15 empirical distribution converges to the true null distribution of the statistic. Thus an approximate  $100(1 - \alpha)\%$  significance level test for circle idiosyncrasy can be conducted by comparing the circle's  $cX^2$  statistic value to the  $(\alpha)$ th quantile of the bootstrapped empirical distribution. Also note that, as a sum of (theoretically) independent random variables, the  $cX^2$  sampling distribution should converge asymptotically to the normal distribution as the number  
20 of observations over which the statistic is computed grows large. We can determine when application of the normal theory is feasible by testing goodness-of-fit of the bootstrapped distribution to the normal, for example using the Kolmogorov-Smirnov statistic.

Under the assumptions of the null hypothesis, the value of the  $cX^2$  can be shown to grow linearly in the total purchase  
25 count of the circle (community) as well as the number of items to recommend (i.e. terms in the  $cX^2$  summation). Since the purchase probabilities are constants under the null hypothesis, these are the only two variables with which the  $cX^2$  grows. So in theory we would want to bootstrap a distribution for each possible  $\langle n, r \rangle$  pair, where  $n$  is the circle's purchase count and  $r$  the number of recommended items. In practice, both  $n$  and  $r$  are random variables which depend on the particular set of random customers we assemble at each iteration of the bootstrap. So we bootstrap various random  
30 group sizes at various lookback horizons, then recover the sampling distributions from the  $\langle n, r \rangle$  values implicitly obtained in the course of each iteration. We can then construct approximate empirical distributions for  $\langle n, r \rangle$  intervals which are large enough to contain enough observations for us to get useful convergence to the true null distribution. With these parameterized approximate sampling distributions available, we conduct a hypothesis test using the sampling distribution whose  $\langle n, r \rangle$  interval contains the values of  $n$  and  $r$  actually obtained for the circle being tested.

35

#### IV. Determination of Optimal Lookback Horizon

Before testing the hypothesis that a particular purchase circle follows the probability model to allocate its purchases across items, we decide how much of the circle's available transaction data to use in computing the censored chi-square test statistic. We choose to utilize data looking sequentially backwards in time, without weighting observations. Thus the question of how much data to use is equivalent for our purposes to asking how many prior days of data to include in the computation. We refer to this number of days as the *lookback horizon* associated with the purchase circle.

In general, the power of a test statistic (the probability the test statistic will detect deviations from the null hypothesis) is a nondecreasing function of the amount of data provided, so using all available data normally won't harm our statistical inferences. There are other drawbacks in our situation, however. First, the stationarity assumption behind the purchase probability estimates is at best only locally correct. The further back in time we look, the more likely it is that nonstationarity in the purchase probabilities will manifest itself in our hypothesis tests. Since this nonstationarity impacts the bootstrap as well, it is actually a pervasive problem that can't be circumvented with simple resampling, and it will tend to cause us to detect circle idiosyncrasies where none actually exist.

Second, without researching the power function of the censored chi-square, we cannot make any statements about the expected power benefits of incrementally larger datasets. In light of this, it makes sense to let computational efficiency dictate the sizes of the datasets used in hypothesis testing. In other words, knowing nothing about the relative value of larger datasets, we will use the smallest dataset which allows a given purchase circle to satisfy the reasonability criterion. Currently this means that the observed count for the 99th percentile of the circle's positive-residual items, ranked by observed count, must be at least 5.

Determining the minimum lookback horizon consistent with this constraint would in general require repeated computations at successively longer horizons for a particular circle. Instead, for computational efficiency, we will forecast a horizon that has high probability of satisfying the constraint, accepting that in expectation some small percentage of circles will fail to satisfy it. The forecast is produced as a side effect of the bootstrap computation (see above). Each random group size we bootstrap over will have iterations at many horizons. At each horizon, some fraction of the iterations will fail the reasonability criterion. We record all such failures. Roughly speaking, the fraction of failures should decrease as lookback horizon increases. Given a purchase circle whose minimum lookback horizon we want to forecast, we find the bootstrap group size it is close to, then pick the shortest horizon which had an acceptable failure rate. If no bootstrapped horizon had an acceptably low rate, we choose the longest horizon and accept that many idiosyncratic circles of that size will escape detection by failing the reasonability criterion.

**WHAT IS CLAIMED IS:**

1. A method of assisting users in selecting items from an electronic catalog of items, the catalog accessible to users of an online store that provides services for allowing users to purchase items from the catalog, the method comprising:
  - 5 providing a database which contains information about a plurality of user communities, wherein different communities represent different subsets of users of the store;
    - tracking online purchases of items from the store by the users to generate purchase history data, and storing the purchase history data in a computer memory;
    - processing at least the purchase history data to identify at least one item which, based on pre-specified criteria, has become popular within a particular community; and
    - 10 electronically notifying members of the community that the at least one item is popular within the community.
  2. The method of Claim 1, wherein electronically notifying members of the community comprises generating a Web page which includes a community-based most popular items list.
  - 15 3. The method of Claim 2, wherein the most popular items list is a bestsellers list.
  4. The method of Claim 1, wherein electronically notifying members of the community comprises automatically generating and sending an email message to members of the community.
  5. The method of Claim 4, wherein the email message contains contact information of at least one member of the community that has purchased an item described in the email message.
  - 20 6. The method of Claim 1, wherein processing the purchase history data to identify at least one item comprises identifying a set of characterizing purchases for the community.
  7. The method of Claim 1, wherein the community is an implicit membership community.
  8. The method of Claim 7, wherein the community is based on email addresses of users.
  9. The method of Claim 1, wherein the community is an explicit membership community.
  - 25 10. The method of Claim 1, wherein the community is derived from an electronic address book of a user.
  11. The method of Claim 1, wherein the community is a composite community which comprises multiple other communities of the database.
  12. A system for assisting users of an online store in selecting items from an electronic catalog of items, the system comprising:
    - 30 at least one database which contains purchase history data for users of the store, and which contains information about a plurality of user communities wherein different communities represent different subsets of users of the store; and
    - a computer process which identifies items that are popular within particular communities of the plurality of communities by analyzing at least the purchase history data, and which notifies users of the store of
    - 35 the items that are popular within particular communities.

13. The system of Claim 12, wherein the process comprises a first process which generates a data store which contains bestselling items lists for at least some of the communities, and a second process which selects items from the table to display to users.

14. The system of Claim 12, further comprising a user interface which allows users to select and join at  
5 least some of the user communities.

15. The system of Claim 12, further comprising a user interface which allows a user to define a composite community that includes multiple communities of the database, and to initiate generation of a popular items list for the composite community.

16. The system of Claim 12, wherein at least some of the communities are implicit membership  
10 communities.

17. The system of Claim 12, wherein at least some of the communities are based on email addresses of users.

18. A method of assisting users in selecting items from an electronic catalog of items, the catalog accessible to users of an online store that provides services for allowing users to purchase items from the catalog, the  
15 method comprising the computer-implemented steps of:

identifying a subset of users of the store that have email addresses that satisfy a particular criteria;

identifying at least one item that is popular among the subset of users, wherein the step of identifying comprises processing purchase history data of at least the subset of users; and

electronically notifying users of the store of a popularity of the at least one item among the subset of  
20 users.

19. The method of Claim 18, wherein identifying a subset of users comprises identifying all users of a selected email domain.

20. The method of Claim 19, wherein the selected email domain is an email domain of a selected company.

21. The method of Claim 18, wherein identifying a subset of users comprises identifying all users of a  
25 selected group of email domains.

22. The method of Claim 18, wherein electronically notifying comprises generating a Web page which includes a list of bestselling items among the subset of users.

23. The method of Claim 18, wherein electronically notifying comprises sending email notification messages to at least some of the users of the subset.

30 24. A method of recommending items from a catalog of items, comprising:

identifying a community of users that represents a subset of a general population of users;

tracking at least one type of user activity that indicates user affinities for particular items of the catalog to generate history data;

processing the history data of the general population of users, including the community of users, to  
35 identifying a set of items that distinguish the community from the general population; and



recommending items from the set of items to members of the community.

25. The method of Claim 24, wherein processing the history data comprises processing purchase history data, and the set of items consists essentially of items purchased by members of the community.

26. The method of Claim 24, wherein tracking at least one type of user activity comprises tracking item  
5 viewing events.

27. The method of Claim 24, wherein the community is an implicit-membership community.

28. A method of assisting users in evaluating items of an electronic catalog of items, the catalog accessible to users of an online store that provides services for allowing users to purchase items from the catalog, the method comprising the computer-implemented steps of:

10 storing contact information for at least some of the users of the store within a computer memory;  
identifying an item to be displayed to a first user;  
identifying a second user that has purchased the item;  
retrieving the contact information for the second user from the computer memory; and  
electronically notifying the first user of the contact information of the second user to allow the first  
15 user to communicate with the second user about the item.

29. The method of Claim 28, wherein identifying the second user comprises:  
identifying a user community of which the first user is a member; and  
determining whether another member of the community has purchased the item.

30. The method of Claim 28, wherein identifying an item to display to the first user comprises:  
20 identifying a community of which the first user is a member; and  
identifying an item that is popular within the community.

31. The method of Claim 30, wherein identifying an item that is popular within the community comprises identifying at least one item which, based on purchases made within the community relative to purchases made within a general user population, distinguishes the community from the general user population.

25 32. The method of Claim 28, wherein electronically notifying comprises incorporating the contact information into a product detail page requested by the first user.

33. The method of Claim 28, wherein electronically notifying comprises sending to the first user an email message which contains the contact information and a description of the product.

34. The method of Claim 28, further comprising generating a data structure which maps items to users  
30 that purchased the items.

35. The method of Claim 28, wherein the contact information includes an email alias for permitting anonymous communications.

36. The method of Claim 28, further comprising presenting to users of the store at least one option screen which permits users to authorize release of contact information to other users on at least one of (a) a user-by-user basis,  
35 and (b) a community-by-community basis.

37. The method of Claim 28, wherein the community is an implicit membership community.
38. The method of Claim 37, wherein the implicit membership community is based on email addresses of users.
39. The method of Claim 28, wherein electronically notifying the first user of the contact information comprises presenting the first user an option to chat online with the second user.
40. A system for assisting users of an online store in evaluating items of an electronic catalog of items, the system comprising:
- a data structure which maps items from the catalog to users that have purchased such items; and
  - a process which responds to an online request by a first user to view a description of an item from the catalog by at least (a) accessing the data structure to identify a second user that has purchased the item, and (b) displaying contact information of the second user to the first user in conjunction with the description.
41. The system of Claim 40, wherein the data structure maps items to users that purchased the items for each of a plurality of communities, and the process uses the data structure to locate a fellow community member that purchased the item.
42. The system of Claim 40, wherein the data structure contains the contact information of users.
43. The system of Claim 40, wherein the contact information includes email aliases for at least some of the users.
44. The system of Claim 40, wherein the contact information includes an option for the first user to chat online with the second user.
45. A method of assisting a first user in evaluating a merchant, comprising:
- identifying a community of which the first is a member;
  - identifying a second user that is a member of the community and that has engaged in business with the merchant; and
  - electronically notifying the first user of the contact information of the second user to allow the first user to communicate with the second user about the merchant.

1/11

File Edit View Go Favorite Help

Back Forw... Stop Refresh Home Search Favorite Print Font Mail

Address

**amazon.com**

## Community Interests-Signup

Hello, Erin Indianer.

Tell us about the communities you belong to, and we will periodically tell you about what others in your communities are buying: (hold down "CTRL" to select more than one):

College/University:

Local community groups:

Local outdoors clubs:

⋮

Professional Organizations:

30

32 [Click here](#) to add a community to the list or to create a private community

36 ☐ Check this box if you would like to know the names and e-mail addresses of others in your communities that have recently purchased the item you are looking at. By selecting this option, you authorize Amazon.com to send your name and e-mail address to other community members. [Click Here](#) to limit your participation to specific communities and/or product categories 40

37 ☐ Check this box if you would like to receive e-mail notifications of hot sellers in your communities. [Click Here](#) to limit your participation to specific communities an/or product categories 41

38 ☐ Check this box if you would like to receive an e-mail notification whenever a member of one of your communities purchases a product, and to allow others in your communities to monitor your purchases (participating communities only). [Click Here](#) to limit your participation to specific communities and/or product categories 42

46

FIG. 1

2/11




FIG. 2

3/11




FIG. 3

4/11





FIG. 4



6/11





FIG. 6



7/11

*FIG. 7A*

8/11




FIG. 7B

9/11




FIG. 8

10/11




FIG. 9

11/11




FIG. 10

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US00/40077

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC(7) :G06F 17/60 US CL :705/26 According to International Patent Classification (IPC) or to both national classification and IPC														
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) U.S. : 705/26, 27, 10, 14 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)														
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>														
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.												
Y, P	US 6,041,311 A (CHISLENKO et al.) 21 March 2000, see the abstract, figs. 1-3.	1-45												
Y, P	US 5,956,693 A (GEERLINGS) 21 September 1999, see the abstract, figs. 4A, 4C.	1-45												
Y, E	US 6,064,980 A (JACOBI et al) 16 May 2000, see the abstract, figs. 1, 3, 6, 7, 11.	1-45												
A, E	US 6,101,486 A (ROBERTS et al) 08 August 2000, see the abstract.	1-45												
A, E	US 6,078,740 A (DETREVILLE) 20 June 2000, see the abstract.	1-45												
A, P	US 6,035,283 A (ROFRANO) 07 March 2000, see the abstract.	1-45												
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.														
<table border="0"> <tr> <td>* Special categories of cited documents:</td> <td>*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</td> </tr> <tr> <td>*A* document defining the general state of the art which is not considered to be of particular relevance</td> <td>*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</td> </tr> <tr> <td>*E* earlier document published on or after the international filing date</td> <td>*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</td> </tr> <tr> <td>*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</td> <td>*A* document member of the same patent family</td> </tr> <tr> <td>*O* document referring to an oral disclosure, use, exhibition or other means</td> <td></td> </tr> <tr> <td>*P* document published prior to the international filing date but later than the priority date claimed</td> <td></td> </tr> </table>			* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	*E* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family	*O* document referring to an oral disclosure, use, exhibition or other means		*P* document published prior to the international filing date but later than the priority date claimed	
* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention													
*A* document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone													
*E* earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art													
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*A* document member of the same patent family													
*O* document referring to an oral disclosure, use, exhibition or other means														
*P* document published prior to the international filing date but later than the priority date claimed														
Date of the actual completion of the international search 26 AUGUST 2000		Date of mailing of the international search report <b>15 SEP 2000</b>												
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230		Authorized officer ROBERT A. WEINHART Telephone No. (703) 308-3900 <i>Eugenio Lopez</i>												

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US00/40077

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A,E	US 6,078,892 A (ANDERSON et al) 20 June 2000, see the abstract.	1-45
A,P	US 5,974,396 A (ANDERSON et al) 26 October 1999, see the abstract.	1-45